



**GMX PROCUREMENT/CONTRACT NO.:** \_\_\_\_\_  
**GMX WORK PROGRAM NO.:** \_\_\_\_\_  
**GMX PROJECT/SERVICE TITLE:** \_\_\_\_\_  
 \_\_\_\_\_

**TRENCH SAFETY**

Section 553.62, Florida Statutes, incorporates the Occupational Safety and Health Administration’s (OSHA) safety standards, 29 CFR s. 1926.650 Subpart P, as the state standard. The Department of Labor and Employment Security may adopt updated or revised versions by rule. Other state or political subdivisions may also have standards that are applicable. If trench excavation will be required on the Project in excess of five (5) feet in depth, the Bidder/Proposer must identify the cost of compliance with the applicable trench safety standards below. If there will be no trench excavation on the Project in excess of five (5) feet in depth, write “not applicable” on the below table.

Trench Safety Measure (Description)		Units of Measure	Quantity	Unit Cost	Extended Cost
A				\$	\$
B				\$	\$
C				\$	\$
D				\$	\$
E				\$	\$
F				\$	\$
Total					\$

If applicable, this certifies that all trench excavation done within the control of the Contractor will be in accordance with all applicable standards and with the specifications, and all applicable sections of the Florida Statutes.